

4 HERBERT BROWN IND. PARK • 50/52 WHITELEY STREET • MILNSBRIDGE  
• HUDDERSFIELD • WEST YORKSHIRE • HD3 4LT • UK  
TEL: 00 44 (0) 1484 512354

## LATEX SEALS

Your Beaver Latex Seals are an integral part of your diving equipment and should be treated with as much care as the rest of your accessories. Your Beaver Latex Seals are designed to provide a water tight seal on your drysuit or other similar garments. Beaver Latex Seals are manufactured in the UK to stringent quality control regulations, giving you a product which is strong, durable and will give years of trouble-free service provided a few basic instructions are adhered to.

MODEL: \_\_\_\_\_

DATE OF PURCHASE: \_\_\_\_\_

PURCHASED FROM: \_\_\_\_\_

## INSTRUCTIONS

1. Always ensure that the Latex Seals you purchase are suitable for the application intended, it is important that the correct type and size is used. Carefully measure the suit and the Latex Seal ensuring that the correct type is used and also measure the relevant ankle, wrist or neck to select the correct size. If you are not sure seek the advice of an authorised Beaver dealer. Latex Seals should only be fitted by a trained and authorised technician.
2. Once you have the correct type and size, carefully prepare the inner face of the seals to be glued with a suitable rough surface to ensure a good surface is available for glueing. Ensure that the original seals are completely removed, leaving a smooth surface to enable replacements to be fitted.
3. Use a 2 part adhesive such as *Beaver Aquabond* to adhere the Latex Seals and carefully apply to the desired area following the adhesive instructions. Neoprene Tape such as *Beaver Aquatape*, should be applied on the inside seams once again following the adhesive instructions. A suitable item should be placed around the section of the suit to retain the shape of the suit.
4. Fine increases to the size of the Latex Seals can be made by carefully cutting using an appropriate cutting tool along the guidelines.
5. To ensure that your Latex Seals remain in good condition they must be stored away from sunlight and heat sources. After fitting, it is recommended that *McNett Seal Saver* is applied regularly. After each use of your suit, wash in clean fresh water and dry thoroughly, store in a cool dry location away from direct sunlight.
6. *Beaver Aquabond*, *Aquatape*, *McNett Seal Saver* and other repair and maintenance products are available from all Beaver dealers.

## CAUTION

*All watersports are potentially hazardous. Before using any watersports equipment you should be properly instructed and trained in its use by a recognised club or organisation.*

**PLEASE RETAIN WITH RECEIPT FOR GUARANTEE PURPOSES**

email: [sales@beaversports.co.uk](mailto:sales@beaversports.co.uk)

web: [www.beaversports.co.uk](http://www.beaversports.co.uk)